



Arable Mark 3

Specifications & Measurements

Hardware Specifications

SKUs
880-0002-02 (Global)
880-0002-07 (Brazil)

Compute System
Processor: Dual core CPU (1 core dedicated to machine learning)
RAM: 64 MB SDRAM
Storage: 1GB embedded flash + 64GB micro-SD card

Power System
USB-C input power: 5V, 2A
Solar panel: 6W
Rechargeable batteries: 47 Wh lithium iron phosphate
Charging temperature: -10°C (14°F) / +65°C (150°F)
Operating temperature: -20°C (-4°F) / +85°C (185°F)

Communication System
Wide area:
LTE-M: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/
B20/B25/B26/B27/B28/B66/B85

NB-IoT*:
B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/
B28/B66/B71/B85

2G: 850/900/1800/1900 MHz
GNSS: GPS/GLONASS/BeiDou/Galileo
Local area: Bluetooth BLE 5.2*: 2.4 GHz

**Hardware enabled, software upgradeable*

Included in Box
Mark 3 device
Bird spikes
USB charging cable
Solar panel and solar panel knob
Zip ties
Cellular and Bluetooth antennas
Start Here card

| | |
|---------------------------|---|
| Ingress Protection Rating | IP67 rated for protection against water and dust ingress |
| Device Dimensions | Dome: 10.5" diameter (26.7 cm) Height of unit with solar panel: 15.5" (39.4 cm) |
| Package Dimensions | 16.9" x 13.9" x 6.2" (42.9 x 35.2 x 15.8 cm) |
| Package Weight | Weight: 6 lbs (2.72 kg) |
| Accessories | Arable Mark 3 Ultrasonic Anemometer Sentek Drill & Drop Soil Moisture Probe Arable Mark 3 Auxiliary Sensor Hub Adapter GEMS Pressure Switch Arable Telescoping Pole Arable Ground Anchor |

Sensor and Camera Measurements

Precipitation**
 Range: Calibrated 0.1 to 50 mm/hr
 Accuracy: Within calibrated range ± 0.4 mm/hr
 Precipitation type: Rain, mixed drizzle/rain (sleet, snow and hail excluded)

Temperature**
 Range: Calibrated -20°C to 60°C (-4°F to 140°F)
 Accuracy: Within calibrated range $\pm 0.5^{\circ}\text{C}$ ($\pm 0.9^{\circ}\text{F}$) / Outside calibrated range $\pm 1.5^{\circ}\text{C}$ ($\pm 2.7^{\circ}\text{F}$)
 Measurement interval: 5 minutes

Relative Humidity
 Range: 1 to 100% RH
 Resolution and units: 0.1% RH
 Accuracy: $\pm 5\%$
 Nominal drift: $< 0.25\%$ RH/year

Pressure
 Range: 26 kPa to 126 kPa absolute pressure;
 Accuracy: ± 0.25 kPa across $0-65^{\circ}\text{C}$
 *0.1 can be achieved based on specific testing environment
 Nominal drift: ± 0.1 kPa/year

Spectrometry
 Four-way net radiometer
 - Upward and downward shortwave sensors (350 to 1100 nm)
 - Upward and downward longwave sensors (3 μm to 14 μm)
 Dual 22 band spectroradiometers spanning 400 nm to 1700 nm
 Dual SWIR band sensors measuring 1600 nm

Camera
 5MP RGB camera

| | |
|------------------|--|
| Composition | 5P + 1 IR Filter |
| EFL | 1.58mm |
| TTL | $5.75 \pm 0.1\text{mm}$ |
| FNO | $2.2 \pm 5\%$ |
| FOV | Vertical: 72° Horizontal: 103° Diagonal: 110° |
| Mate Sensor Size | .25" |
| F/# | 2.5 |
| Auto-Focus | Included |
| Auto-Exposure | Included |
| Color | Included |

**Accuracy at initial release with continuous machine learning model improvements expected over time.

Accessory Measurements

Wind Speed Range: 0.2 - 40 m/s (0.45 - 90 mph)
Resolution: 0.5 m/s (1.1 mph)
Sampling interval: 3 sec

Wind Direction Range: 0 - 360°
Resolution: 5°
Sampling interval: 3 sec

Soil Moisture Number of sensors: 1, 3, 6, 9 or 12 (10 cm spacing)
Resolution (Volumetric Water Content): 1:10000
Accuracy: ±0.03% vol

Soil Temperature Number of sensors: 1, 3, 6, 9 or 12 (10 cm spacing)
Resolution: 0.3° C
Accuracy: ±2° C @ 25° C

Soil Salinity Number of sensors: 1, 3, 6, 9 or 12 (10 cm spacing)
Resolution (Electric Conductivity): 1:3000

Irrigation Pressure Range: 4 - 8 psi (0.28 - 0.55 bar)
Accuracy: ±0.35 psi (0.024 bar) +2% of setting

Derived Measurements - Environmental

Vapor Pressure Deficit

Vapor pressure deficit (kPa) is the difference – or deficit – between the amount of moisture in the air and how much moisture the air can hold when it is saturated. VPD is recognized as the evaporative driving force for water transport.

Sunshine Duration

Sunshine duration (hrs) is the length of time each day where direct solar irradiance is greater than 120 W m^{-2} . This is based on the World Meteorological Organization (WMO) guidelines.

Dew Point Temperature

The dew point is the temperature the air needs to be cooled to (at constant pressure) in order to achieve a relative humidity (RH) of 100%.

Sea Level Pressure

Sea level pressure (kPa) is empirically derived from the measured pressure, air temperature, and elevation, as well as from the gravitational acceleration and gas constants.

Derived Measurements - Plant

| | |
|---|--|
| Reference Evapotranspiration (ET _o) | Evapotranspiration is the amount of water a plant loses in a day. It is the combined loss of water from the processes of evaporation (the movement of water from surfaces or water bodies to the atmosphere) and transpiration (the loss of water vapor through the plant's stomata to the atmosphere). ET _o is the hypothetical value under a grass reference surface. |
| Crop Evapotranspiration (ET _c) | Crop evapotranspiration, or ET _c , is the total evaporation and transpiration estimated for your specific crop. The value is achieved by multiplying the reference ET (ET _o) by a crop coefficient (K _c NDVI). The K _c NDVI is dynamically derived by measuring the NDVI reflectance (greenness) of the crop growing in your field and captures the crop development throughout the growing season. The resulting ET _c value represents the water losses (evaporation and transpiration) specific to your crop system. |
| Growing Degree Days | Growing degree days (°C-day or °F-day) measure how much heat a crop has received during the season. Since temperature influences many biological processes that determine health and vigor, GDD is strongly correlated to plant development. It is a calculation that represents the passage of physiological time based on temperature. Different biological thresholds and the start of accumulation dates are used for each crop and varietal. Cumulative growing degree days (CGDD) are the sum of GDDs since the beginning of the season, as specified by the user. |
| Growth Stages | Growth stages are changes in the phenological stages of a crop. Plant growth stages can help you predict crop vegetative development during the life cycle based on the accumulation of growing degree days. Arable keeps a running list of crops and cultivars and the phenological models observed and modeled by many researchers worldwide for use in our web and mobile apps. After calculating GDD for each crop, we can apply it to the known phenological stage. |
| Leaf Wetness | Hourly leaf wetness is binary, where 1 is defined as wet and 0 as dry. If any length of time within a given hour is deemed wet, then that entire hour is classified as 1. Daily leaf wetness represents the number of whole hours that were defined as wet, determined by summing the results of each hour. Arable calculates leaf wetness based on measured relative humidity and the rate of relative humidity change. |

| | |
|--------------------|---|
| Water Balance | Water balance represents the total amount of water coming into a site through precipitation and irrigation and out of a site via ETc. This can be used to understand the trend of plant-water availability in order to plan irrigation events. |
| Crop Water Deficit | Crop water deficit is the difference between a site's water loss (ETc) and incoming water through precipitation. |
| Heat Stress | Heat stress counts the number of daylight hours during which the canopy temperature is above a stress threshold for the crop (default 36° C / 96°F). |
| NDVI | NDVI (normalized difference vegetation index) is a generalized index to evaluate green vegetation's overall vigor and is broadly correlated to the canopy leaf area index (LAI). The calculation is performed using the NIR and red band reflectances. This is based on the papers by Tucker (1979) and Rouse et al. (1974). |
| Chlorophyll Index | Chlorophyll index is a spectral index correlated with nitrogen uptake during peak greenness. The calculation is performed using the comparison of specific spectral ranges that correlate to chlorophyll content based on the paper by Gitelson & Merzlyak (2005). |
| Kc-NDVI | The crop coefficient is derived from the vegetation cover as measured by NDVI using Arable's spectrometers. Given that NDVI is specific to the crop, Kc-NDVI represents the actual conditions of the crop canopy. |
| Chill Hours | A chill hour is the amount of chilling received by a plant at 45°F / 7.2°C. The chilling requirement is the total number of hours required during the winter for a particular cultivar to break dormancy and produce flowers. |
| Daily Crop Images | Images are provided daily at noon from the embedded 5MP RGB camera of the Mark 3. |
| Canopy Temperature | Canopy temperature is the temperature reported from a downward-facing semi-hemispherical infrared radiometer. If the surface under the unit is completely uniform (e.g., a continuous grass carpet) this measurement represents the temperature of that surface. If the surface under the unit is not completely uniform, this measurement represents the average temperature of all surfaces in the field of view. |

Derived Measurements - Water

| | |
|-------------------------------|---|
| Irrigation Start & End Times | The start and end times of the irrigation is taken from the opened/closed state of the pressure switch connected to the irrigation drip line. |
| Total Irrigation Run Time | The irrigation run time is the sum of times when the pressure switch is open across the measurement period. |
| Last Irrigation Run Time | The date and amount when an irrigation event was last observed using data from the pressure switch or from data that was manually entered on the Water tab for that site. |
| Applied Irrigation | The applied irrigation is the irrigation runtime multiplied by the flow rate and then divided by the site area. If multiple pressure switches are associated with a site, the amount is a sum total. |
| Proximity to Refill Threshold | The distance to the soil moisture refill point for a site is expressed as a percentage. This equals the mean soil moisture for the measurement period (as a percentage of field capacity) minus the refill threshold. |
| Irrigation to Replace ETC | The irrigation hours needed to meet the defined Replacement ETC taking into account any set Replacement ET % percentage for the growth stage. |